


**USG DUROCK™ BRAND
PERFORMANCE FLOORING
2019 NEW PRODUCTS**

**USG DUROCK™ LSP™ LIQUID SURFACE PROFILER
USG DUROCK™ CRACK REPAIR COMPOUND
USG DUROCK™ CST™ MOISTURE VAPOR REDUCER
USG DUROCK™ ULTRADRY™ SELF-LEVELING UNDERLAYMENT
USG DUROCK™ PCO™ WHITE SELF-LEVELING TOPPING**

usgperformanceflooring.com

NEW USG DUROCK™ BRAND PERFORMANCE FLOORING PRODUCTS

USG leads the way in performance flooring with new products for 2019. From new construction to major renovation or minor repairs – USG has your solution.

PRODUCT	APPLICATION	FEATURES AND BENEFITS
USG DUROCK™ LSP™ LIQUID SURFACE PROFILER		
 <p>Liquid surface profiler</p>	Dust-free alternative to cleaning and profiling concrete for indoor, outdoor, horizontal, above and below grade applications	<ul style="list-style-type: none"> Patented, biodegradable concrete cleaner and surface profiler Dust-free substitute for grinding, shot blasting and acid etching Low-fume formula Prepares concrete for moisture mitigation systems, pourable underlayment, floor patches, sealers and coatings Self-neutralizing formula Easy to use and apply; up to 50% faster than mechanical preparation methods Fully biodegradable, non-toxic and eco-friendly
USG DUROCK™ CRACK REPAIR COMPOUND		
 <p>Polyurea crack filler</p>	Ideal for repairing cracks and voids in concrete; may also be used over wood, fiberglass and asphalt	<ul style="list-style-type: none"> Ideal for repairing cracks in concrete substrates Fast-setting - allows for foot traffic in as little as 10 minutes Install coating, toppings or floor coverings in as little as 30 minutes Innovative formulation allows for rapid curing in temperatures below zero Easy mixing, smooth finish Durable and strong - up to 6,000 psi (41.4 MPa)
USG DUROCK™ CST™ MOISTURE VAPOR REDUCER		
 <p>Moisture mitigation system</p>	Single coat, spray on application mitigation system used over concrete	<ul style="list-style-type: none"> Reactive chemistry creates a permanent membrane 2-4 mm below the surface Assists in reducing MVER by 5+ lbs. Reduces RH by ≥ 10%; maintains a consistent pH at the surface level Maintains surface profile for optimal bond of patching and leveling compounds and coatings Fast drying - in as little as 30 minutes, depending on environmental conditions Can be applied 24 hours after concrete is poured
USG DUROCK™ ULTRADRY™ SELF-LEVELING UNDERLAYMENT		
 <p>High-performance self-leveler</p>	Interior use in commercial, institutional and rehab construction; ideal for fast-track renovation	<ul style="list-style-type: none"> Fast-track solution for commercial and institutional repair and renovation Allows for application of ceramic tiles in 4 hours and most floor coverings in 12 hours; wood in 24 hours Featheredge to 5 in. (127 mm) neat No mechanical preparation required for most applications Fast and easy to mix
USG DUROCK™ PCO™ WHITE SELF-LEVELING TOPPING		
 <p>High-performance polishable concrete overlay</p>	Designed to receive integral or topical pigments to provide a decorative, polished wear surface for interior applications over concrete	<ul style="list-style-type: none"> A Portland Cement blend that offers wear surface properties similar to concrete Fast application and fast setting - allows for quick return of normal trade traffic Smooth, with excellent polishing characteristics No mechanical preparation required for most applications

For detailed instructions including application restrictions and how to prepare the subfloor, see the corresponding product submittal sheets and SDSs at usg.com and usgperformanceflooring.com.

CB5261-USG-ENG/1-19

© 2019 USG Corporation and/or its affiliates.
All rights reserved.
Printed in the USA

Manufactured by or for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

800 USG.4YOU
800 (874-4968)
usgperformanceflooring.com
usg.com

PRODUCT INFORMATION

See usgperformanceflooring.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, CST, DUROCK, LSP, PCO, ULTRADRY, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.