






**USG DUROCK™ BRAND  
PERFORMANCE FLOORING  
2019 NEW PRODUCTS**

**USG DUROCK™ LSP™ LIQUID SURFACE PROFILER  
USG DUROCK™ CST™ MOISTURE VAPOR REDUCER  
USG DUROCK™ ULTRADRY™ SELF-LEVELING UNDERLAYMENT  
USG DUROCK™ PCO™ WHITE SELF-LEVELING TOPPING  
USG DUROCK™ GENIUS™ FLOORING ADHESIVE**

[usgperformanceflooring.com](http://usgperformanceflooring.com)

# NEW USG DUROCK™ BRAND PERFORMANCE FLOORING PRODUCTS

USG leads the way in performance flooring with new products for 2019. From new construction to major renovation or minor repairs – USG has your solution.

PRODUCT	APPLICATION	FEATURES AND BENEFITS
<b>USG DUROCK™ LSP™ LIQUID SURFACE PROFILER</b>		
 <p>Liquid surface profiler</p>	Dust-free alternative to cleaning and profiling concrete for indoor, outdoor, horizontal, above and below grade applications	<ul style="list-style-type: none"> <li>Patented, biodegradable concrete cleaner and surface profiler</li> <li>Proprietary catalyst reacts with free minerals at the concrete paste layer, bringing them and other contaminants to the surface for easy removal</li> <li>Dust-free substitute for grinding, shot blasting and acid etching</li> <li>Low-fume formula</li> <li>Prepares concrete for moisture mitigation systems, pourable underlayment, floor patches, sealers and coatings</li> <li>Self-neutralizing formula</li> <li>Easy to use and apply; up to 50% faster than mechanical preparation methods</li> </ul>
<b>USG DUROCK™ CST™ MOISTURE VAPOR REDUCER</b>		
 <p>Moisture mitigation system</p>	Single coat, spray on application mitigation system used over concrete	<ul style="list-style-type: none"> <li>Reactive chemistry creates a permanent membrane 2-4 mm below the surface</li> <li>Ideal for concrete with MVER up to 12 lbs.</li> <li>Reduces RH by ≥ 10%; maintains a consistent surface level pH</li> <li>Maintains surface profile for optimal bond of patching and leveling compounds and coatings</li> <li>Fast drying - in as little as 30 minutes, depending on environmental conditions</li> <li>Can be applied 24 hours after concrete is poured</li> </ul>
<b>USG DUROCK™ ULTRADRY™ SELF-LEVELING UNDERLAYMENT</b>		
 <p>High-performance self-leveler</p>	Interior use in commercial, institutional and rehab construction; ideal for fast-track renovation	<ul style="list-style-type: none"> <li>Fast-track solution for commercial and institutional repair and renovation</li> <li>Allows for application of ceramic tiles in 4 hours and most floor coverings in 12 hours; wood in 24 hours</li> <li>Featheredge to 5 in. (127 mm) neat</li> <li>No mechanical preparation required for most applications</li> <li>Fast and easy to mix</li> </ul>
<b>USG DUROCK™ PCO™ WHITE SELF-LEVELING TOPPING</b>		
 <p>High-performance polishable concrete overlay</p>	Designed to receive integral or topical pigments to provide a decorative, polished wear surface for interior applications over concrete	<ul style="list-style-type: none"> <li>A Portland Cement blend that offers wear surface properties similar to concrete</li> <li>Fast application and fast setting - allows for quick return of normal trade traffic</li> <li>Smooth, with excellent polishing characteristics</li> <li>No mechanical preparation required for most applications</li> </ul>
<b>USG DUROCK™ GENIUS™ FLOORING ADHESIVE</b>		
 <p>Universal pressure sensitive floor-covering adhesive</p>	Bond carpet tiles, non-patterned broadloom, sheet vinyl, resilient (LVT, LVP, VCT) and sport flooring	<ul style="list-style-type: none"> <li>For use on all grades of concrete, metal, wood, fiberglass and terrazzo</li> <li>Tolerates up to 99% RH (ASTM F2170); up to 10 lbs. MVER (ASTM F1869); and pH levels up to 12 (ASTM F710)</li> <li>Releasable or semi-permanent</li> <li>Can be used wet, semi-wet or clear</li> <li>High shear strength 45+ lbs., average peel 5+ lbs.</li> <li>CRI Green Label Plus Certified – low VOCs</li> </ul>

For detailed instructions including application restrictions and how to prepare the subfloor, see the corresponding product submittal sheets and SDSs at [usg.com](http://usg.com) and [usgperformanceflooring.com](http://usgperformanceflooring.com).

## CB5261-USG-ENG/rev. 10-19

© 2019 USG Corporation and/or its affiliates.  
All rights reserved.  
Printed in the USA

Manufactured by or for  
United States Gypsum Company  
550 West Adams Street  
Chicago, IL 60661

800 USG.4YOU  
800 (874-4968)  
[usgperformanceflooring.com](http://usgperformanceflooring.com)  
[usg.com](http://usg.com)

## PRODUCT INFORMATION

See [usgperformanceflooring.com](http://usgperformanceflooring.com) for the most up-to-date product information.

## TRADEMARKS

The trademarks USG, CST, DUROCK, GENIUS, LSP, PCO, ULTRADRY, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

## NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs

associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

## NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Contact your USG Company office or representative for information.

## SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.